
- CONCRETE PAD AND CHAIN LINK FENCE BY GENERAL CONTRACTOR. REFER TO SHEET A-I.
- (2) CORE DRILL EXISTING CONCRETE FLOOR FOR NEW 4" CHILLED WATER LINES AND POWER CONDUIT TO DROP DOWN INTO MECHANICAL ROOM BELOW. PROVIDE SHEET METAL FLANGE AROUND PIPING AND SEAL WATER TIGHT. ALL NEW EQUIPMENT AND PIPING TO BE INSTALL AS MUCH AS POSSIBLE BEFORE EXISTING EQUIPMENT IS SHUT-DOWN AND PIPING IS REMOVED TO MINIMIZE SHUT-DOWN TIME
- (3) CONNECT NEW 4" CHILLED WATER SUPPLY AND RETURN LINES TO CORRESPONDING 6" LINES ABOVE EXISTING CHILLER. FIELD VERIFY EXACT SIZE AND LOCATION OF EXISTING PIPING. OPEN EXISTING SHUT-OFF VALVE AFTER NEW CHILLER IS OPERATIONAL AND CLOSE EXISTING SHUT-OFF VALVE TO EXISTING CHILLER. ALL NEW EQUIPMENT AND PIPING TO BE INSTALL AS MUCH AS POSSIBLE BEFORE EXISTING EQUIPMENT IS SHUT-DOWN AND PIPING IS REMOVED TO MINIMIZE SHUT-DOWN TIME
- (4) EXISTING AIR SEPARATOR, CIRCULATING PUMPS, CHEMICAL FEED TANK AND EXPANSION TANK TO REMAIN. PROTECT ALL PIPING AND EQUIPMENT DURING CONSTRUCTION.




CHILLED WATER SYSTEM PIPING DIAGRAM

	CHILLER SCHEDULE											
SYM.	TYPE	NOMINAL	CHILLER								LBS	REMARKS
		TONS	EWT	LMT	CHAR	MCA	COP	MIN. GPM	MAX. GPM	PD	LDJ	REMARKS
4	PACKAGED	120	55°F	45°F	208/60/3	522	10.4	140	360	15'	6000#	TRANE MODEL CGAMI20 HIGH EFFICIENCY CHILLER WITH SCROLL COMPRESSORS

ALTERNATE BID NOTES:

- A DISCONNECT AND REMOVE ALL EXISTING REFRIGERANT PIPING AND CONTROL WIRING WHICH SERVE EXISTING CONDENSERS. REMOVE FROM COURTYARD, DOWN THRU CONCRETE FLOOR, AND IN MECHANICAL ROOM BELOW. EXISTING CIRCUIT OUT TO LAWN AREA IS TO REMAIN. OWNER TO CAPTURE AND STORE ALL EXISTING R-22 REFRIGERANT. COORDINATE WORK SCHEDULE WITH OWNER. ALL NEW EQUIPMENT AND PIPING TO BE INSTALL AS MUCH AS POSSIBLE BEFORE EXISTING EQUIPMENT IS SHUT-DOWN AND PIPING IS REMOVED TO MINIMIZE SHUT-DOWN
- (B) DISCONNECT AND REMOVE EXISTING METAL PIPE COVER IN COURTYARD. DISCONNECT AND REMOVE EXISTING CHILLER FROM EXISTING REFRIGERANT PIPING, POWER WIRING AND CONDUITS AND CONTROL WIRING AND CONDUITS. ALL NEW EQUIPMENT AND PIPING TO BE INSTALL AS MUCH AS POSSIBLE BEFORE EXISTING EQUIPMENT IS SHUT-DOWN AND PIPING IS REMOVED TO MINIMIZE SHUT-DOWN TIME.
- (C) DISCONNECT AND REMOVE EXISTING INDOOR CHILLER AND ALL ASSOCIATED REFRIGERANT PIPING, AND CONTROLS. ALL NEW EQUIPMENT AND PIPING TO BE INSTALL AS MUCH AS POSSIBLE BEFORE EXISTING EQUIPMENT IS SHUT-DOWN AND PIPING IS REMOVED TO MINIMIZE SHUT-DOWN TIME.
- (D) DISCONNECT AND REMOVE EXISTING VERTICAL AIR COOLED CONDENSING UNIT FOR EXISTING REFRIGERANT PIPING AND CONTROL WIRING. ALL NEW EQUIPMENT AND PIPING TO BE INSTALL AS MUCH AS POSSIBLE BEFORE EXISTING EQUIPMENT IS SHUT-DOWN AND PIPING IS REMOVED TO MINIMIZE SHUT-DOWN TIME.



DRWN. BY:	CKD. BY:				
M JENSEN	D <u>SUDWEEKS</u>				
JOB NO.	DATE:				
17059	FEB. 2018				

OF: **SIX**

Systems

Engineered

ssocial

18223 - CHILLER REPLACEN AL ARTS BUILDII VERSITY